



## SAFE DEPOSIT LOCKERS TYPE BF4



### **Burglary protection**

Roburs Safe Deposit Lockers type BF4 are tested and certified by SSF, Svenska Stöldskyddsföreningen in accordance with SSF 1048-2 Bankfack-Krav och Provning.

### **Description**

The body is a rigid welded unit built of cold rolled steel.

The locker doors are made of specially ground aluminium. Each door has a number-plate with the number of the locker.

Lock and bolt work are built into the door. Therefore this is even on the inside.

Hinges are concealed

The lockers come in vertical columns which are secured to each other in the vault.

Bases are recessed and have means for easy adjustment of height for levelling.

### **Locking systems**

These systems vary with regard to the method the bank intends to use for controlling access to the lockers.

The systems may be mechanical or electrical and are described in separate leaflets. One thing however, is common. Only the customer with his personal key can operate the lock which withdraws the bolt and gives access to the locker.

### **Finish**

Locker doors in silver anodized aluminium.

Body in grey stove enamel.

### **Inner containers**

Each locker has an inner container.

For measurements please see page three

# Standard locker combinations

There are 5 standard locker heights. These are based on a modular system, where each module is 25 mm.

These heights may be combined as required within the space available between base and cornice.

<b>Model BF4 - 1830</b>							
Figure	Locker height - mm					Qty of lockers	
	50	75	125	175	300		
01	33					33	Total height 1830 mm
02	24	6				30	Base 37 mm
03	15	12				27	For lockers 1650 mm
04	9	16				25	Width 320 mm
05	22	4	2			28	Depth 492 mm
06	19	6	2			27	Weight 90 kg
07	11	8	4			23	
08	8	7	3	2		20	
09	16	5		1	1	23	
10	12	2	2	2	1	19	
11	6	5	5	2		18	
12	2		2	4	2	10	
13	2		1	3	3	9	
14	2			2	4	8	
15		2			5	7	
X	Please choose your own locker combination.						
DW	Locker height - mm						For lockers 1725 mm
	300	325	425		500		Width 640 mm
		4	1				Weight 190 kg

Higher lockers are made on special orders.

<b>Model BF4 - 2030</b>							
Figure	Locker height - mm					Qty of lockers	
	50	75	125	175	300		
01	37					37	Total height 2030 mm
02	28	6				34	Base 37 mm
03	19	12				31	For lockers 1850 mm
04	7	20				27	Width 320 mm
05	22	5	3			30	Depth 492 mm
06	16	9	3			28	Weight 100 kg
07	11	9	5			25	
08	7	11	4	1		23	
09	4	4	8	2		18	
10	16	2	2	2	1	23	
11	7	4	3	3	1	18	
12	4	10	2	2	1	19	
13	5	3	1	2	3	14	
14			1	3	4	8	
15				2	5	7	
X	Please choose your own locker combination.						
DW	Locker height - mm						For lockers 1925 mm
	300	325	425		500		Width 640 mm
		1	5				Weight 200 kg

Higher lockers are made on special orders.

Height - mm	Qty of modules	Space available for lockers between base and cornice.		
		Model	For lockers - mm	Numb. of modules
50	2			
75	3	BF4 - 1830	1650	66
125	5	BF4 - 2030	1850	74
175	7	BF4 - 2230	2050	82
300	12			

<b>Model BF4 - 2230</b>							
Figure	Locker height - mm					Qty of lockers	
	50	75	125	175	300		
01	41					41	Total height 2230 mm
02	32	6				38	Base 37 mm
03	20	14				34	For lockers 2050 mm
04	5	24				29	Width 320 mm
05	26	5	3			34	Depth 492 mm
06	16	10	4			30	Weight 110 kg
07	15	9	5			29	
08	5	14	6			25	
09	3	4	10	2		19	
10	19	5	2	1	1	28	
11	11	4	3	3	1	22	
12	11	8	2	2	1	24	
13	8	6	2	2	2	20	
14	5	4	3	3	2	17	
15		1	1	2	5	9	
X	Please choose your own locker combination.						
DW	Locker height - mm						For lockers 2125 mm
	300	325	425		500		Width 640 mm
		5			1		Weight 220 kg

Higher lockers are made on special orders.



<b>Inner container - dimensions</b>			
Locker	Height - mm	Width - mm	Depth - mm
50	43	260	445
75	66	260	445
125	118	260	445
175	168	260	445
300	293	260	445



[www.robursafe.com](http://www.robursafe.com)

---

We reserve the right to alter the specification without prior notice.



**Head office**  
**Robur Safe AB**

Lundbyvägen 8  
SE-310 50 SLÖINGE  
Phone: +46 346 260 260  
Fax: +46 346 260 222

[info@robursafe.com](mailto:info@robursafe.com)

[www.robursafe.com](http://www.robursafe.com)